

# ARGuard™ Multi-Purpose LS GL-5 Gear Oil

PROD. CODE  
7731

ARGuard™ Multi-Purpose LS GL-5 Gear Oil is a high performance, multi-grade, extreme-pressure, multi-purpose gear lubricant specially formulated to satisfy the needs of most limited slip rear axles. It is friction modified to help eliminate the stick-slip chatter associated with low speed, high torque operation of limited slip differentials.

ARGuard™ Multi-Purpose LS GL-5 Gear Oil is formulated with quality base oils and carefully selected additives which provide excellent anti-wear protection under heavy loads.

## FEATURES & BENEFITS

- Maximum protection against scuffing and wear
- Excellent load carrying capacity
- Outstanding rust and corrosion protection

## INDUSTRY & OEM SPECIFICATIONS

- API GL-5
- SAE J2360

## APPLICATIONS

ARGuard™ Multi-Purpose LS GL-5 Gear Oil can be used in heavy duty and conventional limited slip differentials in heavy duty and light duty trucks as well as passenger cars.

METHOD	DESCRIPTION	TYPICAL
	LBS/GAL	7.39
D4052	API GRAVITY	28.3
D445	VISCOSITY @ 40 °C, cSt	140.8
D445	VISCOSITY @ 100 °C, cSt	14.5
D2270	VISCOSITY INDEX	100
D1500	COLOR	7.0
D92	FLASH POINT, °F	420

Mixing with incompatible chemicals may be hazardous. This product is for industrial use only. Safety data sheets are available upon request. No warranties expressed or implied, including patent warranties or warranties of merchantability or fitness for a particular purpose, are made by American Refining Group, Inc., with respect to products described or information set forth herein. Nothing contained herein shall constitute a permission or recommendation to practice any invention covered by a patent without a license from the owner of the patent.



[amref.com](http://amref.com) | 814.368.1200

